

XIAMETER(R) RTV-4136-M BASE (BASE information is below)

1. IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY

1.1	Product Name:	XIAMETER(R) RTV-4136-M BASE (BASE information is below)		
1.2	Manufacturer's Product Code:	04107132		
1.3	Chemical Classification:	Liquid Silicone Rubber		
1.4	Use:	Silicone rubber base		
1.5	Company Details:			
	Manufacturer/Supplier:	Dow Corning (Thailand) Limited		
	Address:	177/1 Bangkok Union Insurance Building, 17th Floor, Soi Anumarnrajthon 1, Surawong Road, Suriyawong, Bangrak, Bangkok 10500		
	Telephone Number:	(+66) 2634 6700	Fax Number:	(+66) 2634 6799
	Emergency Telephone Number:	(65) 6542 9595 (24 hours)		
	Contact Person:	EHS, QA, Production or Distribution Center Department Head		

2. COMPOSITION / INFORMATION ON INGREDIENTS

2.1	Chemical characterization:	Mixture		
2.2	Hazardous Ingredients:			
	<u>Chemical Name</u>	<u>CAS No.</u>	<u>% (w/w)</u>	<u>Risk Phrases</u>
	Quartz	14808-60-7	30 - 60	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
	Dimethylvinylated and trimethylated silica	68988-89-6	10 - <30	Not hazardous.
<p>Classified as hazardous according to the Harmful Chemical Lists as defined in Clause 2 of Notification of Ministry of Interior, Re: Working Safety relating to harmful chemicals* (*Government Gazette Vol.108, Part 167, dated 24 September B.E. 2534) and European Commission Directive 1999/45/EC (Article 3[3]).</p>				

3. HAZARDS IDENTIFICATION

3.1	Overall Hazard Classification:	Not hazardous.
3.2	Hazard Information:	Not hazardous.
3.3	Precautionary Information:	Avoid contact with skin and eyes.
3.4	Signs and Symptoms of Overexposure:	No significant adverse effects from a single exposure expected from normal use.

4. FIRST AID MEASURES

4.1	Eyes:	Immediately flush with water.
------------	--------------	-------------------------------

XIAMETER(R) RTV-4136-M BASE (BASE information is below)

4.2	Skin:	No first aid should be needed.
4.3	Inhalation:	No first aid should be needed.
4.4	Ingestion:	Get medical attention.
4.5	Comments:	Treat symptomatically.
4.6	Note to physicians:	Treat symptomatically. For further information, the medical practitioner should refer to the phone numbers in Section 1.

5. FIRE-FIGHTING MEASURES

5.1	Hazardous Properties:	None.
5.2	Extinguishing Media:	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO ₂), dry chemical or water spray. Water can be used to cool fire exposed containers.
5.3	Special Fire Fighting Procedures and Equipment:	Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool. Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals.
5.4	Hazardous Combustion Products:	Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Metal oxides. Quartz. Formaldehyde.
5.5	Unsuitable Extinguishing Media:	None established.

6. ACCIDENTAL RELEASE MEASURES

6.1	Personal Precautions:	Avoid eye contact. Do not take internally.
6.2	Environmental Precautions:	Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers.
6.3	Methods for Cleaning up:	Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protective equipment recommendations described in this MSDS. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which laws and regulations are applicable.

7. HANDLING AND STORAGE

7.1	Handling Precautions:	Use with adequate ventilation. Avoid eye contact. Do not take internally. Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.
7.2	Storage Conditions:	Use reasonable care and store away from oxidizing materials.
7.3	Unsuitable Packaging Materials:	None established.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

XIAMETER(R) RTV-4136-M BASE (BASE information is below)

8.1 Industrial Hygiene Standards:

<u>Ingredients</u>	<u>CAS No.</u>	<u>Exposure Limits</u>
Quartz	14808-60-7	Thailand: TWA 2.4 MPPCF Respirable dust. TWA 0.1 mg/m ³ Respirable dust. TWA 0.3 mg/m ³ Total dust. OSHA PEL (final rule): TWA 10 mg/m ³ % respirable SiO ₂ +2; TWA 30 mg/m ³ % total dust SiO ₂ +2 and ACGIH TLV: TWA 0.025 mg/m ³ respirable fraction.
Dimethylvinylated and trimethylated silica	68988-89-6	Dow Corning guide: 5 mg/m ³ Ceiling (as dust).

8.2 Engineering Controls

Local Ventilation: None should be needed.
General Ventilation: Recommended.

8.3 Personal Protective Equipment for Routine Handling

Respiratory protection: No respiratory protection should be needed.

Suitable Respirator: None should be needed.

Eye protection: Use proper protection - safety glasses as a minimum.

Hand protection: No special protection needed.

Skin protection: Washing at mealtime and end of shift is adequate.

Hygiene Measures: Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.

8.4 Personal Protective Equipment for Spills

Respiratory protection: No respiratory protection should be needed.

Eye protection: Use proper protection - safety glasses as a minimum.

Skin protection: Washing at mealtime and end of shift is adequate.

Precautionary Measures: Avoid eye contact. Do not take internally. Use reasonable care.

Comments: If this product is heated to > 180 degrees C, trace quantities of formaldehyde may be released, and adequate ventilation is required.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding aerosol inhalation toxicity, please refer to the guidance document regarding the use of silicone-based materials in aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.

XIAMETER(R) RTV-4136-M BASE (BASE information is below)

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1	Physical Form:	Viscous Liquid
9.2	Color:	Beige
9.3	Odor:	Not available
9.4	pH:	Not determined.
9.5	Solubility in Water:	Not determined.
9.6	Boiling Point:	> 100 °C
9.7	Melting Point:	Not determined.
9.8	Flash Point:	> 100 °C (Closed Cup)
9.9	Autoignition temperature:	Not determined.
9.10	Explosive properties:	No
9.11	Oxidizing properties:	No
9.12	Vapor Pressure @ 25°C:	Not determined.
9.13	Specific Gravity:	1.29
9.14	Octanol/water partition coefficient:	Not determined.
9.15	Vapour Density (air=1):	Not determined.
9.16	Viscosity:	130000 cSt
9.17	Upper Flammability Limit:	Not determined.
9.18	Lower Flammability Limit:	Not determined.

The above information is not intended for use in preparing product specifications.

10. STABILITY AND REACTIVITY

10.1	Stability:	Stable.
10.2	Reactivity	
	Conditions to Avoid:	None.
	Materials to Avoid:	Can react with strong oxidising agents.
	Hazardous Decomposition Products:	Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Metal oxides. Quartz. Formaldehyde.
	Hazardous Polymerization :	Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

11.1	Possible Health Effects:	
	Acute	
	Eyes:	Direct contact may cause temporary redness and discomfort.
	Skin:	No significant irritation expected from a single short-term exposure.
	Ingestion:	Low ingestion hazard in normal use.
	Inhalation:	No significant effects expected from a single short-term exposure.
	Chronic	
	Skin:	No known applicable information.
	Ingestion:	Repeated ingestion or swallowing large amounts may injure internally.
	Inhalation:	No known applicable information.
11.2	Sensitizing Effects:	None known.
11.3	Mutagenic Effects:	None known.
11.4	Reproductive Effects:	None known.
11.5	Carcinogenic Effects:	None known.

XIAMETER(R) RTV-4136-M BASE (BASE information is below)

11.6 Other Health Hazard Information: No known applicable information.

The above listed potential effects of overexposure are based on actual data, the results of studies performed upon similar compositions, component data, and/or expert review of the products.

12. ECOLOGICAL INFORMATION

12.1 Environmental Fate and Distribution:

Siloxanes are removed from water by sedimentation or binding to sewage sludge. In soil, siloxanes are degraded.

12.2 Environmental Effects:

No adverse effects on aquatic organisms.

Bioaccumulation: No bioaccumulation potential.

12.3 Fate and Effects in Waste Water Treatment Plants:

Removed > 90% by binding onto sewage sludge. No adverse effects on bacteria. The siloxanes in this product do not contribute to the BOD.

12.4 Additional Environmental Information:

Degradation: Additional environmental information on the silicone component is available on request.

13. DISPOSAL CONSIDERATIONS

13.1 Product Disposal: Dispose of in accordance with local regulations.

13.2 Packaging Disposal: Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

14.1 Road and Rail Transport:

Not applicable.

14.2 Sea Transport (IMDG):

Not subject to IMDG code.

14.3 Air Transport (IATA):

Not subject to IATA regulations.

15. REGULATORY INFORMATION

15.1 Hazardous Substance Act, B.E. 2535:

XIAMETER(R) RTV-4136-M BASE (BASE information is below)

Chemical Name

CAS No.

Not available.

15.2 Chemical Inventories:

AICS:	All ingredients listed or exempt.
DSL:	All chemical substances in this material are included on or exempted from the DSL.
IECSC:	All ingredients listed or exempt.
EINECS:	All ingredients listed or exempt.
ENCS/ISHL:	All components are listed on ENCS/ISHL or its exempt rule.
KECL:	All ingredients listed, exempt or notified.
PICCS:	All ingredients listed or exempt.
TSCA:	All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.
HSNO:	All ingredients listed or exempt.

16. OTHER INFORMATION

Contact Point: EHS, QA, Production or Distribution Center Department Head
Prepared by: Dow Corning (Thailand) Limited

This information is offered in good faith as typical values and not as a product specification. No warranty, expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

XIAMETER(R) is a trademark of Dow Corning Corporation

<http://www.xiameter.com>